(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 21 March 2002 (21.03.2002)

(10) International Publication Number WO 02/22388 A1

(51) International Patent Classification7:

(21) International Application Number: PCT/US01/28369

B60K 1/02

(22) International Filing Date:

13 September 2001 (13.09.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/230,933 60/238,016 13 September 2000 (13.09.2000) US 6 October 2000 (06.10.2000)

(71) Applicant: PHILLIPS MACHINE SERVICE, INC. [US/US]; Harper Industrial Park, P.O. Box 1245, Beckley, WV 25802-1245 (US).

(72) Inventors; and

Inventors/Applicants (for US only): ALLEN, Claude, R. [US/US]; 609 Temple Street, Daniels, WV 25832 (US). CUSHMAN, Thomas, S. [US/US]; 120 Daniel Street, Beckley, WV 25801 (US). HICKOK, Jimmy, A. [US/US]; P.O. Box 466, Mabscott, WV 25871 (US). MCWHORTER, Purnal, L. [US/US]; 107 Magnolia Lane, Daniels, WV 25832 (US).

(74) Agent: KAGEN, Alan, M.; Nixon & Vanderhye, P.C., Suite 800, 1100 North Glebe Road, Arlington, VA 22201-4714 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BATTERY POWERED SHUTTLE CAR



(57) Abstract: A battery powered shuttle car (10) incorporates features and components that facilitate use and operation and effect efficient application in a mining environment. The shuttle car (10) incorporates at least one battery (20) that is secured to the vehicle frame (11) between one of a left front wheel (17) and a left rear wheel (17) or the right front wheel (17) and the right rear wheel (17). A battery change-over mechanism (51) facilitates battery replacement. Additionally, the shuttle car (10) may be provided with an integral discharge end (81) having a substantially fixed height (82). A full load indicator mechanism (83) provides an indication when the conveyor (16) is substantially full to maximize use and operation of the shuttle car (10).